

LAS3001 si, LAS3002 si, LAS3003 si & LAS3009 si Door Bottom Seals

Medium Duty



Description

Door bottom and meeting stile seals ideal for acoustic and smoke containment.

Key benefits

Simple, effective sealing solution.
Easily retrofitted to existing door assemblies.
Durable, hard wearing silicone rubber gaskets.

Approvals

Smoke: Conforms with BCA Specification C3.4 smoke sealing requirements.

Durability: Long term mechanical test, completing 1,000,000 cycles without failure.

Standard lengths

1m and 2.1m. Other lengths to special order.

Gap sizes

LAS3001 si – 6mm/13mm.

LAS3002 si – 10mm/17mm.

LAS3003 si – 7mm/13mm.


LAS3009 si – 12mm/18mm.

Fixing method


Face-fixed, semi-rebated or fully rebated.
Fixing screws are supplied.
Fixing holes are pre-drilled.
Once the aluminium carrier is fixed, the rubber gasket slides easily into place.
Note: these seals cannot be adjusted once fitted.

Finishes


Silver anodised aluminium with grey silicone rubber insert.




LAS3001 si



LAS3003 si



LAS3002 si



LAS3009 si



LAS3001 si door bottom seal (shown with LAS4002 threshold plate)