


LAS7005 si Perimeter Seal

Medium Duty



LAS7005 si

Description

A robust stop mounted compression seal incorporating an anodised aluminium carrier fitted with fire rated silicone rubber gasket and non-shrink, click-fit cover strip. The seal is fitted to the head and jambs of the door frame to create an effective seal between the frame and the door face.

Key benefits

Compact and effective acoustic seal that can easily be retrofitted to existing door assemblies.
 Fitted with high performance fire rated silicone rubber gasket.
 Supplied with slotted fixing holes for accurate positioning and easy adjustment.
 Non-shrink, click fit cover strip conceals the fixing points.

Approvals

Fire: Tested in accordance with AS1530.4 on proprietary fire doors.

Sound: Acoustically tested in accordance with ISO10140-2 and AS/NZS717.1 with ratings up to 31Rw on appropriate rated assemblies.

Standard lengths

1m, 2.1m and 2.75m.

Single doorset pack (SDP): (1 x 1m, 2 x 2.1m)

Long single doorset pack (LSDP): (1 x 1m, 2 x 2.75m)

Double doorset pack (DDP): (3 x 2.1m)

Long double doorset pack (LDDP): (1 x 2.1m, 2 x 2.75m).

Fixing method

Screw fixed to the door frame with supplied screw pack.

Gap sizes

Accommodates and seals gaps from 0mm to 10mm.

Finishes

Silver anodised aluminium with grey silicone rubber gasket and click-fit cover strip.



LAS7005 si