Self-adhesive Seals




The seals below are superior quality, self-adhesive weather-strip seals for doors and windows. Quick and easy to install, they are DIY products which work well in eliminating draughts, rattles and cushioning applications.









Min/Max Gap: 3mm to 5mm (user determined).

Fixing: Self adhesive. Note: Contact surface must be clean, smooth and if painted, well cured.

Seal: White or grey open cell urethane foam.

Sizes: 5m coil.


Approvals: Energy NCC Pt. 3.12.3.3 & J3.4.

RP14a









Min/Max Gap: 3mm to 5mm (user determined).

Fixing: Self adhesive. Note: Contact surface must be clean, smooth and if painted, well cured.

Seal: White or grey open cell urethane foam.

Sizes: 5m coil.

Approvals: Energy NCC Pt. 3.12.3.3 & J3.4.

19


RP14b











Min/Max Gap: 8mm to 11mm (user determined).

Fixing: Self adhesive. Note: Contact surface must be clean, smooth and if painted, well cured.

Seal: White open cell urethane foam.

Sizes: 2.5m coil.

Approvals: Energy NCC Pt. 3.12.3.3 & J3.4.






RP61











Min/Max Gap: 3mm to 5mm (user determined).

Fixing: Self adhesive. Note: Contact surface must be clean, smooth and if painted, well cured.

Seal: Grey polypropylene.

Sizes: 5m coil.

Approvals: Energy NCC Pt. 3.12.3.3 & J3.4.



RP48




















Min/Max Gap: 3mm to 5mm (user determined).

Fixing: Self adhesive. Note: Contact surface must be clean, smooth and if painted, well cured.

Seal: White, brown or grey EPDM closed cell sponge.

Sizes: 5m coil pack (2 x 2.5m), jumbo reel (2 x 50m).

Approvals: Energy NCC Pt. 3.12.3.3 & J3.4.

RP59















Location: Perimeter of doors and windows.

Min/Max Gap: 2mm to 4mm (user determined).

Fixing: Self adhesive. Note: Contact surface must be clean, smooth and if painted, well cured.

Seal: White, brown or grey EPDM closed cell sponge.

Sizes: 5m coil pack (2 x 2.5m), jumbo reel (2 x 50m).

Approvals: Energy NCC Pt. 3.12.3.3 & J3.4.

RP108

























Location: Multi-purpose (user determined).

Min/Max Gap: 6mm to 8mm (user determined).

Fixing: Self adhesive. Note: Contact surface must be clean, smooth and if painted, well cured.

Seal: White or grey EPDM closed cell sponge.

Sizes: 2m coil pack.

Approvals: Energy NCC Pt. 3.12.3.3 & J3.4.



