

# Astragals

## Meeting Stile Seals



### RP71



An astragal seal designed for plain or rebated meeting stiles of timber double doors where a centre latch bolt may be required or, where both doors are active. The unique quiet fin of the RP71 is effective in acoustic and weather applications. Two RP71 seals are installed on to the one door stile which allows space for a latch between the two seals.

The legs of the seals can be checked out to accommodate the latch bolt front plate providing a continuous seal.

*Note: Minimum door thickness subject to centre latch and dimensions of morticed door bottom seals.*

**Location:** Meeting stiles of double butt hinged and centre pivot double acting doors.

**Min/Max Gap:** 3mm to 4mm.

**Finish:** Satin clear (silver), bronze anodised aluminium (15µm) or paint at extra cost.

**Fixing:** Screw fix. Colour matched zinc plated, cross recess head CSK S.T. screws supplied. Fixing holes are pre-drilled and countersunk.


**Seal:** Black polypropylene pile with felt weather fins.

**Sizes:** Available in stock lengths.

#### Approvals

**Acoustic AUS/NZ:** NCC Spec. F5.5.  
**UK/EU:** Approved Document E. Rated to BS EN ISO 717-1.

**Energy** NCC Pt. 3.12.3.3 & J3.4.



### RP71Si



A medium temperature smoke astragal seal designed for plain or rebated meeting stiles of timber double doors where a centre latch bolt may be required or, where both doors are active. The seal is achieved by a pair of silicon fins. Two RP71Si seals are installed on to the one door stile which allows space for a latch between the two seals.

The legs of the seals can be checked out to accommodate the latch bolt front plate providing a continuous seal.

*Note: Minimum door thickness subject to centre latch and dimensions of morticed door bottom seals.*

**Location:** Meeting stiles of double butt hinged and centre pivot double acting doors.

**Min/Max Gap:** 3mm to 5mm.

**Finish:** Satin clear (silver), bronze, black anodised aluminium (15µm) or paint at extra cost.

**Fixing:** Screw fix. Colour matched zinc plated, cross recess head CSK S.T. screws supplied. Fixing holes are pre-drilled and countersunk.

**Seal:** RP371Si. Grey or black silicon rubber (SE).

**Sizes:** Available in stock lengths.

#### Approvals

**Acoustic AUS/NZ:** NCC Spec. F5.5.  
**UK/EU:** Approved Document E. Rated to BS EN ISO 717-1.

**Fire** Gasket flammability index 1 when tested to AS1530.2.

**Smoke** NCC Spec. C3.4. AS1530.7 & BS EN 1634-3. Meets smoke leakage rates specified in AS6905 & EN 13501-2 "Sa", "Sm".

**Energy** NCC Pt. 3.12.3.3 & J3.4.

